

LOW-LEVEL ACCESS

NPA35

Non-Powered Access

Easy Operation



STANDARD FEATURES

- 1.5m platform height, 3.5 m working height;
- 150 kg safe working load (1 person)
- Compact-only 0.75m wide, passes easily through standard doorways;
- Large 0.72 m x 0.60 m platform size
- Only 1.2m x 0.75 m working footprint
- Easy access gate
- Virtually maintenance free
- No batteries to charge or mains
- Stop wherever you want up to 3.5m working height.
- Easy to deploy, safer to use
- Safer Alternative to Ladders and Steps

Safety features

- Gone are the days of climbing steps or podiums, no more slips, trips or having to balance!
- It's so easy, fast and efficient to use, intuitive.
- Lifting automatic brake
- The platform automatically closes the door

Energy Saving

Environmental Friendly

IMPORTANT

We are continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.



Email: sales@cqliften.com

<https://www.cqliften.com>

WhatsApp: +86 13736163658

LOW-LEVEL ACCESS

OPERATING DIMENSIONS

Maximum working height:	3.50 m
Maximum platform height:	1.50 m
Platform dimensions:	0.72 m x 0.60 m
Working foot print:	1.08 m x 0.84 m
Safe working load:	150 kg (1 person plus tools)
Maximum manual force:	200N
Maximum gradient for operation:	3 degrees
Maximum wind force:	Internal/External, 12.5 m/s
Maximum castor point load:	145 kg
Sound pressure level:	Less than 70dBa
Length:	1.08 m
Width:	0.75 m
Height:	1.55m
Weight	220kg



POWER OPTIONS

No batteries to charge or mains power consumption.

Construction: Heavy duty fabricated steel

Safety:

CE & ANSI marked, complies with applicable European legislation including the Machinery Directive using the EN280 & ANSI design standard.

Options

Narrow basket for suspended ceiling grid access.

Pipe Carrying kit (max 2" pipe).

Tool tray.

Foam buffer kit.



IMPORTANT

We are continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight.

Specifications may change to meet country standards or with the addition of optional equipment.



Email: sales@cqliften.com

<https://www.cqliften.com>

WhatsApp: +86 13736163658